

1. Which type of mezzanine flooring should you select for your needs?

Look at the chart below to see a summary of product strengths and weaknesses:

Rank of Products: 6 = Best, 1 = Worst Rating

	Plywood OSB	Plywood/OSB with HDPE Laminate	Bar Grate	Concrete	UV Coated Particle Board	ResinDek [®]
Material Cost	6	3	2	1	4	5
Wheel Load Cap	1	2	4	6	3	5
Tolerances	2	1	4	3	6	6
Delamination Resistance	1	2	6	6	6	6
Scratch Resistance	1	5	6	5	2	3
ESD Issues	4	1	5	3	2	6
Cleanability	1	3	6	4	3	6
Warranty	1	3	1	1	3	6
Price Volatility	2	3	1	5	5	5
Customer Satisfaction	1	2	4	4	4	6
Total Score	20	26	39	38	38	55

2. Which ResinDek product grade is right for your application?

ResinDek Panels Are Available in 7 Grades:

Panel Grade	Live & Dead Pallet Jack Loads Permitted
ResinDek [®] XLD ₅₀	Foot Traffic and up to 1,250 lbs. Total Load
ResinDek [®] LD ₅₀	Foot Traffic and up to 2,000 lbs. Total Load
ResinDek [®] LD	Foot Traffic and up to 2,000 lbs. Total Load
ResinDek [®] MD	Foot Traffic and up to 3,000 lbs. Total Load
ResinDek [®] HD	Foot Traffic and up to 4,500 lbs. Total Load
ResinDek [®] Max	Foot Traffic and up to 8,000 lbs. Total Load
ResinDek [®] Xspan [®] (no corrugated required)	16" (on center) o.c. up to 3,000 lbs 24" o.c. 2,700 lbs. 32" o.c. 2,300 lbs 40" o.c. 2,000 lbs.

3. Which ResinDek product finish is right for your application?

Jobsite Requirement	Gray Diamond Seal [®]	Clear Diamond Seal [®]	ResinDek [®] ESD	ResinDek [®] Unfinished (UF)
Cleanable Surface	X	X	X	
Superior Stain Resistance	X	X	X	
Skid Resistant Surface	X	X	X	
Showcase Look	X	X	X	
High Gloss Floor	X	X	X	
Superior Scratch Resistance	X	X	X	
Economical Finish	X	X		
Warranty	X	X	X	X
Static Controlled Floor			X	

ResinDek[®] Mezzanine Floor Panels



Product Name	Live Dead Pallet Jack Limits	Thickness	Finishes Available		
			Unfinished	GDS, CDS	ESD
ResinDek [®] XLD ₅₀	up to 1,250 lbs	1/2"	■	■	■
ResinDek [®] LD ₅₀	up to 2,000 lbs	1/2"	■	■	■
ResinDek [®] LD	up to 2,000 lbs.	3/4"	■	■	■
ResinDek [®] MD	up to 3,000 lbs.	3/4"	n/a	■	■
ResinDek [®] HD	up to 4,500 lbs.	3/4"	n/a	■	■
ResinDek [®] MAX	Up to 8,000 lbs.	1-1/2"	n/a	■	■
ResinDek [®] Xspan [®]	Up to 3,000 lbs - No Corrugated	1-1/8"	n/a	■	■

Finishes Available

Gray Diamond Seal[®]
Clear Diamond Seal[®]
ESD Certified Static Control

Options

Invisi-Loc[®] fasteners
T & G Configurations
No Added Formaldehyde



All ResinDek Products can contribute towards earning points for LEED[®] qualified buildings.



www.resindek.com