

With our Electrostatic Dissipative Finish, ResinDek<sup>®</sup> ESD mezzanine floor panels provide an outstanding static control solution for mezzanine floors, shelving systems and workstations.

- ESD protection for electrically sensitive devices such as laptops, barcode scanners, servo-drive motors, and pick-to-light systems that are common in distribution centers
- Eliminate expensive computer downtime caused by electrostatic discharges
- Prevent uncomfortable static shocks to employees with a grounded surface
- Available on all panel grades of ResinDek

ResinDek<sup>®</sup> ESD panels have been extensively tested by the testing firm of Stephen Halperin & Associates and have been found to be in compliance with the following ESD Association Specifications:

#### ANSI/ESD S7.1-2005

Resistive Characterization of Materials—Floor Materials.

#### ANSI/ESD S20.20-2007

Protection of Electrical and Electronic Parts, Assemblies and Equipment.

#### ANSI/ESD STM97.1-2006

Floor Materials and Footwear—Resistance

Measurement in Combination with a Person.

#### Testing Results are Summarized as Follows:

- Average point-to-point resistance = 6.6 x 10<sup>6</sup> ohms
- Average point-to-ground resistance = 7.8 x 10<sup>6</sup> ohms
- ResinDek<sup>®</sup> ESD mezzanine floor panels generated less than 10 volts with static controlled footwear, and experienced a rapid voltage decay from 5,000 volts to less than 50 volts in under .50 seconds

ResinDek ESD also provides a stain, scratch and skid resistant surface that won't delami-



nate like other decking materials. It installs easily over corrugated metal B-decking with recommended fastening systems.



## ResinDek<sup>®</sup> Mezzanine Floor Panels



#### Finishes Available

Product Name	Live Dead Pallet Jack Limits	Thickness	Finishes Available		
			Unfinished	GDS, CDS	ESD
ResinDek <sup>®</sup> XLD <sub>50</sub>	up to 1,250 bs	1/2"	■	■	■
ResinDek <sup>®</sup> LD <sub>50</sub>	up to 2,000 bs	1/2"	■	■	■
ResinDek <sup>®</sup> LD	up to 2,000 lbs.	3/4"	■	■	■
ResinDek <sup>®</sup> MD	up to 3,000 lbs.	3/4"	n/a	■	■
ResinDek <sup>®</sup> HD	up to 4,500 lbs.	3/4"	n/a	■	■
ResinDek <sup>®</sup> MAX	Up to 8,000 lbs.	1-1/2"	n/a	■	■
ResinDek <sup>®</sup> Xspan <sup>®</sup>	Up to 3,000 lbs - No Corrugated	1-1/8"	n/a	■	■

#### Finishes Available

Gray Diamond Seal<sup>®</sup>  
Clear Diamond Seal<sup>®</sup>  
ESD Certified Static Control

#### Options

Invisi-Loc<sup>®</sup> fasteners  
T & G Configurations  
No Added Formaldehyde



All ResinDek Products can contribute towards earning points for LEED<sup>®</sup> qualified buildings.



[www.resindek.com](http://www.resindek.com)